

The new DDX Valves for Deluge, Preaction, & Dry System Installations

June 2006

Dear Valued Customer:

Reliable is committed and dedicated to providing you with new and exciting products. We are proud to announce our latest product development - the **DDX Valves**.

- 4" (100mm), 6" (150mm), and 165mm
- cULus Listed and FM Approved for deluge, preaction, & dry applications
- DDX Valve is 250 psi (17,2 bar) rated
- Extremely lightweight - weighs 50% less than the BX Valve
- Both ends are grooved
- A 3:1 releasing ratio with a latched open clapper. No PORV.
- A system side check valve is not required for preaction or dry applications
- Only one main drain connection
- External reset
- No priming water is required for preaction or dry applications
- The DDX-LP dry system uses the same low pressures as the LDX dry system
- Dry systems may be hydrostatically tested with the clapper closed
- Quick installing segmented, preassembled or loose trim

For more information on the DDX Valves, please refer to Bulletins 510 (Deluge System) and 357 (DDX-LP Dry Pipe Valve System).

Thank you again for choosing Reliable for your fire protection needs. We look forward to providing you with the latest technology, quality, and service.

Sincerely,



Michael R. Fee
V.P. Marketing & Sales Operations



With its very compact trim, you'll want to wrap your arms around this valve!