

New Storage Sprinklers!

October 2006

Dear Valued Customer:

Continuing in our tradition of providing you with the latest technology, quality and service, Reliable is proud to announce two new Storage Sprinklers - **N252 EC** and **J168 Sprinklers**.

The **N252 EC** with a K-Factor of 25.2, is an Extended Coverage Pendent and Recessed Pendent Sprinkler for Density/Area Design.

- Approved for coverage up to 196 square feet (14' x 14') for Extra Hazard and Storage Applications.
- Can be installed directly on the piping for exposed pipe systems. Sprig-ups are not required for larger diameter piping.
- cULus Listed for a minimum of deflector to commodity distance of 36" and for unabstructed or non-combustible obstructed construction.
- Complies with the criteria for protection of retail stores as described in NFPA 2002, section 12-7.1
- For more information, refer to Bulletin 008 and for pricing see page S-72 in our Price Book.

The **J168** has a K-Factor of 16.8 and is a new Control Mode, Density/Area Upright Sprinkler.

- Primarily for Extra Hazard and storage Occupancies as designed and installed under NFPA 13 requirements.
- Can allow reduced design area, higher storage, reduced ceiling clearance to storage, and other savings in sprinkler design.
- Uses the robust Model G solder capsule that has been installed in millions of sprinklers over the last 30 years.
- For more information, refer to Bulletin 011 and for pricing, see page S-72 in our Price Book.

Thank you again for choosing Reliable - your one source for all your fire protection needs.

Sincerely,



Michael R. Fee
V.P. Marketing & Sales Operations