



F1-56 UPRIGHT

- K-Factor = 5.6 (80)
- **SIN RA1325**
- See Bulletin 071



F1-80 UPRIGHT

- K-Factor = 8.0 (115)
- **SIN RA6222**
- See Bulletin 062

| Part Number | Short Code | Temperature | | Finish | List Price |
|--|------------|-------------|-------|------------|------------|
| MODEL F1-56 UPRIGHT K5.6 (80) THREADS 1/2" (15MM) RA1325 | | | | | |
| AA131132S9 | F56U0BN | 135°F | 57°C | Brass | £ 26.96 |
| AA132132S9 | F56U0CN | 135°F | 57°C | Chrome | £ 32.87 |
| AA138732S9 | F56U0WN | 135°F | 57°C | White | £ 37.99 |
| AA151132S9 | F56U1BN | 155°F | 68°C | Brass | £ 26.96 |
| AA152132S9 | F56U1CN | 155°F | 68°C | Chrome | £ 32.87 |
| AA158732S9 | F56U1WN | 155°F | 68°C | Poly White | £ 37.99 |
| AA171132S9 | F56U5BN | 175°F | 79°C | Brass | £ 26.96 |
| AA172132S9 | F56U5CN | 175°F | 79°C | Chrome | £ 32.87 |
| AA178732S9 | F56U5WN | 175°F | 79°C | White | £ 37.99 |
| AA201132S9 | F56U2BN | 200°F | 93°C | Brass | £ 26.96 |
| AA202132S9 | F56U2CN | 200°F | 93°C | Chrome | £ 32.87 |
| AA208732S9 | F56U2WN | 200°F | 93°C | Poly White | £ 37.99 |
| AA281132S9 | F56U3BN | 286°F | 141°C | Brass | £ 26.96 |
| AA282132S9 | F56U3CN | 286°F | 141°C | Chrome | £ 32.87 |
| AA288732S9 | F56U3WN | 286°F | 141°C | Poly White | £ 37.99 |
| AA361132S9 | F56U6BN | 360°F | 182°C | Brass | £ 30.32 |
| AA362132S9 | F56U6CN | 360°F | 182°C | Chrome | £ 36.07 |
| AA368732S9 | F56U6WN | 360°F | 182°C | White | £ 41.30 |
| MODEL F1-80 UPRIGHT K8.0 (115) THREADS 3/4" (20MM) RA6222 | | | | | |
| A1131134S8 | FU0LBN | 135°F | 57°C | Brass | £ 33.16 |
| A1132134S8 | FU0LCN | 135°F | 57°C | Chrome | £ 41.18 |
| A1138734S8 | FU0LWN | 135°F | 57°C | Poly White | £ 49.20 |
| A1151134S8 | FU1LBN | 155°F | 68°C | Brass | £ 33.16 |
| A1152134S8 | FU1LCN | 155°F | 68°C | Chrome | £ 41.18 |
| A1158734S8 | FU1LWN | 155°F | 68°C | Poly White | £ 49.20 |
| A1171134S8 | FU5LBN | 175°F | 79°C | Brass | £ 33.16 |
| A1172134S8 | FU5LCN | 175°F | 79°C | Chrome | £ 41.18 |
| A1178734S8 | FU5LWN | 175°F | 79°C | Poly White | £ 49.20 |
| A1201134S8 | FU2LBN | 200°F | 93°C | Brass | £ 33.16 |
| A1202134S8 | FU2LCN | 200°F | 93°C | Chrome | £ 41.18 |
| A1208734S8 | FU2LWN | 200°F | 93°C | Poly White | £ 49.20 |
| A1281134S8 | FU3LBN | 286°F | 141°C | Brass | £ 33.16 |
| A1282134S8 | FU3LCN | 286°F | 141°C | Chrome | £ 41.18 |
| A1288734S8 | FU3LWN | 286°F | 141°C | Poly White | £ 49.20 |
| A1361134S8 | FU6LBN | 360°F | 182°C | Brass | £ 33.16 |
| A1362134S8 | FU6LCN | 360°F | 182°C | Chrome | £ 41.18 |
| A1368734S8 | FU6LWN | 360°F | 182°C | White | £ 49.20 |

6880050100 WW2 Wrench, W2, Pendent, Upright, HSW £ 114.28



F1 56 UPRIGHT

- K-Factor = 80 (5.6)
- **SIN RA1325**
- See Bulletin 013

| Part Number | Short Code | Temperature | | Finish | List Price |
|---|------------|-------------|-------|------------|------------|
| MODEL F156 UPRIGHT K5.6 (80) THREADS 1/2" (15MM) RA1325 | | | | | |
| AA131132R9 | F56U0B | 135°F | 57°C | Brass | £ Call |
| AA132132R9 | F56U0C | 135°F | 57°C | Chrome | £ Call |
| AA138732R9 | F56U0W | 135°F | 57°C | Poly White | £ 37.99 |
| AA151132R9 | F56U1B | 155°F | 68°C | Brass | £ Call |
| AA152132R9 | F56U1C | 155°F | 68°C | Chrome | £ Call |
| AA158732R9 | F56U1W | 155°F | 68°C | Poly White | £ 37.99 |
| AA171132R9 | F56U5B | 175°F | 79°C | Brass | £ Call |
| AA172132R9 | F56U5C | 175°F | 79°C | Chrome | £ Call |
| | | °F | °C | | £ Call |
| AA201132R9 | F56U2B | 200°F | 93°C | Brass | £ Call |
| AA202132R9 | F56U2C | 200°F | 93°C | Chrome | £ Call |
| AA208732R9 | F56U2W | 200°F | 93°C | White | £ Call |
| AA281132R9 | F56U3B | 286°F | 141°C | Brass | £ Call |
| AA282132R9 | F56U3C | 286°F | 141°C | Chrome | £ 32.87 |
| AA288732R9 | F56U3W | 286°F | 141°C | Poly White | £ Call |
| AA361132R9 | F56U6B | 360°F | 182°C | Brass | £ Call |
| AA362132R9 | F56U6C | 360°F | 182°C | Chrome | £ Call |
| | | °F | °C | | £ Call |
| MODEL F156 UPRIGHT K5.6 (80) BSPT THREADS 1/2" (15MM) RA1325 | | | | | |
| AA131132R2 | F56U0BM | 135°F | 57°C | Brass | £ 26.96 |
| | | °F | °C | | £ Call |
| AA138732R2 | F56U0WM | 135°F | 57°C | Poly White | £ 37.99 |
| AA151132R2 | F56U1BM | 155°F | 68°C | Brass | £ 26.96 |
| AA152132R2 | F56U1CM | 155°F | 68°C | Chrome | £ 32.87 |
| AA158732R2 | F56U1WM | 155°F | 68°C | Poly White | £ 37.99 |
| AA171132R2 | F56U5BM | 175°F | 79°C | Brass | £ 26.96 |
| AA172132R2 | F56U5CM | 175°F | 79°C | Chrome | £ 32.87 |
| AA178732R2 | F56U5WM | 175°F | 79°C | White | £ 37.99 |
| AA201132R2 | F56U2BM | 200°F | 93°C | Brass | £ 26.96 |
| AA202132R2 | F56U2CM | 200°F | 93°C | Chrome | £ 32.87 |
| AA208732R2 | F56U2WM | 200°F | 93°C | Poly White | £ 37.99 |
| AA281132R2 | F56U3BM | 286°F | 141°C | Brass | £ 26.96 |
| AA282132R2 | F56U3CM | 286°F | 141°C | Chrome | £ 32.87 |
| AA288732R2 | F56U3WM | 286°F | 141°C | Poly White | £ 37.99 |
| AA361132R2 | F56U6BM | 360°F | 182°C | Brass | £ 30.32 |
| AA362132R2 | F56U6CM | 360°F | 182°C | Chrome | £ 36.07 |
| | | °F | °C | | £ Call |

6880050100 WW2 Requires Model W2 Sprinkler Wrench £ 114.28



F1 LO UPRIGHT

- Upright
- **SIN R1722**
- See Bulletin 117

| Part Number | Short Code | Temperature | | Finish | List Price |
|--|------------|-------------|-------|------------|------------|
| MODEL F1 LO UPRIGHT K8.0 (115) THREADS 3/4" (20MM) R1722 | | | | | |
| A113113498 | FU0LB | 135°F | 57°C | Brass | £ 33.16 |
| A113213498 | FU0LC | 135°F | 57°C | Chrome | £ 41.18 |
| A113873498 | FU0LW | 135°F | 57°C | White | £ 49.20 |
| A115113498 | FU1LB | 155°F | 68°C | Brass | £ 33.16 |
| A115213498 | FU1LC | 155°F | 68°C | Chrome | £ 41.18 |
| A115873498 | FU1LW | 155°F | 68°C | White | £ 49.20 |
| A117113498 | FU5LB | 175°F | 79°C | Brass | £ 33.16 |
| A117213498 | FU5LC | 175°F | 79°C | Chrome | £ 41.18 |
| A117873498 | FU5LW | 175°F | 79°C | Poly White | £ 49.20 |
| A120113498 | FU2LB | 200°F | 93°C | Brass | £ 33.16 |
| A120213498 | FU2LC | 200°F | 93°C | Chrome | £ 41.18 |
| A120873498 | FU2LW | 200°F | 93°C | Poly White | £ 49.20 |
| A128113498 | | 286°F | 141°C | Brass | £ 33.16 |
| A128213498 | FU3LC | 286°F | 141°C | Chrome | £ 41.18 |
| A128873498 | FU3LW | 286°F | 141°C | White | £ 49.20 |
| A136113498 | FU6LB | 360°F | 182°C | Brass | £ 33.16 |
| A136213498 | FU6LC | 360°F | 182°C | Chrome | £ 41.18 |
| A136873498 | FU6LW | 360°F | 182°C | White | £ 49.20 |
| MODEL F1 LO UPRIGHT K8.0 (115) BSPT THREADS 3/4" (20MM) R1722 | | | | | |
| A113113495 | FU0LBM | 135°F | 57°C | Brass | £ 33.16 |
| A113213495 | FU0LCM | 135°F | 57°C | Chrome | £ 41.18 |
| A113873495 | FU0LWM | 135°F | 57°C | White | £ 49.20 |
| A115113495 | FU1LBM | 155°F | 68°C | Brass | £ 33.16 |
| A115213495 | FU1LCM | 155°F | 68°C | Chrome | £ 41.18 |
| A115873495 | FU1LWM | 155°F | 68°C | Poly White | £ 49.20 |
| A117113495 | FU5LBM | 175°F | 79°C | Brass | £ 33.16 |
| A117213495 | FU5LCM | 175°F | 79°C | Chrome | £ 41.18 |
| A117873495 | FU5LWM | 175°F | 79°C | White | £ 49.20 |
| A120113495 | FU2LBM | 200°F | 93°C | Brass | £ 33.16 |
| A120213495 | FU2LCM | 200°F | 93°C | Chrome | £ 41.18 |
| A120873495 | FU2LWM | 200°F | 93°C | White | £ 49.20 |
| A128113495 | FU3LBM | 286°F | 141°C | Brass | £ 33.16 |
| A128213495 | FU3LCM | 286°F | 141°C | Chrome | £ 41.18 |
| A128873495 | FU3LWM | 286°F | 141°C | Poly White | £ 49.20 |
| A136113495 | FU6LBM | 360°F | 182°C | Brass | £ 33.16 |
| A136213495 | FU6LCM | 360°F | 182°C | Chrome | £ 41.18 |
| A136873495 | FU6LWM | 360°F | 182°C | White | £ 49.20 |

6880050100 WW2 Requires Model W2 Sprinkler Wrench £ 114.28



F1 28 UPRIGHT

- K-Factor = 2.8 (40)
- **SIN RA1321**
- See Bulletin 066



F1 42 UPRIGHT

- K-Factor = 4.2 (60)
- **SIN RA1323**
- See Bulletin 067

| Part Number | Short Code | Temperature | | Finish | List Price |
|---|------------|-------------|-------|------------|------------|
| MODEL F128 UPRIGHT K 2.8 (40) THREADS 1/2" (15MM) RA1321 | | | | | |
| AA151124S9 | F28U1BN | 155°F | 68°C | Brass | £ 40.78 |
| AA152124R9 | F28U1C | 155°F | 68°C | Chrome | £ Call |
| AA158724R9 | F28U1W | 155°F | 68°C | Poly White | £ Call |
| AA171124S9 | F28U5BN | 175°F | 79°C | Brass | £ 40.78 |
| AA172124R9 | F28U5C | 175°F | 79°C | Chrome | £ 48.02 |
| AA178724R9 | F28U5W | 175°F | 79°C | Poly White | £ 51.60 |
| AA201124S9 | F28U2BN | 200°F | 93°C | Brass | £ 40.78 |
| AA202124R9 | F28U2C | 200°F | 93°C | Chrome | £ Call |
| AA208724R9 | F28U2W | 200°F | 93°C | White | £ Call |
| AA281124S9 | F28U3BN | 286°F | 141°C | Brass | £ 40.78 |
| AA282124R9 | F28U3C | 286°F | 141°C | Chrome | £ 48.02 |
| AA288724R9 | F28U3W | 286°F | 141°C | Poly White | £ 51.60 |
| MODEL F142 UPRIGHT K4.2 (60) THREADS 1/2" (15MM) RA1323 | | | | | |
| AA131128R9 | F42U0B | 135°F | 57°C | Brass | £ Call |
| AA132128R9 | F42U0C | 135°F | 57°C | Chrome | £ Call |
| AA138728R9 | F42U0W | 135°F | 57°C | White | £ 51.60 |
| AA151128R9 | F42U1B | 155°F | 68°C | Brass | £ Call |
| AA152128R9 | F42U1C | 155°F | 68°C | Chrome | £ Call |
| AA158728R9 | F42U1W | 155°F | 68°C | Poly White | £ Call |
| AA171128R9 | F42U5B | 175°F | 79°C | Brass | £ Call |
| AA172128R9 | F42U5C | 175°F | 79°C | Chrome | £ Call |
| AA178728R9 | F42U5W | 175°F | 79°C | White | £ 51.60 |
| AA201128R9 | F42U2B | 200°F | 93°C | Brass | £ Call |
| AA202128R9 | F42U2C | 200°F | 93°C | Chrome | £ Call |
| AA208728R9 | F42U2W | 200°F | 93°C | White | £ 51.60 |
| AA288728R9 | F42U3BN | 286°F | 141°C | White | £ 40.78 |
| AA282128R9 | F42U3C | 286°F | 141°C | Chrome | £ Call |
| AA288728R9 | F42U3W | 286°F | 141°C | White | £ 51.60 |
| AA362128R9 | F42U6C | 360°F | 182°C | Chrome | £ 51.32 |
| AA368728R9 | F42U6W | 360°F | 182°C | White | £ 55.26 |

6880050100 WW2 Wrench, W2, Pendent, Upright, HSW £ 114.28



F1-56SS PENDENT

- K-Factor = 5.6 (80)
- **SIN RA6414**
- See Bulletin 064
- Stainless Steel



F1-80SS UPRIGHT

- K-Factor = 8.0 (115)
- **SIN RA6424**
- See Bulletin 064
- Stainless Steel

F1-56SS UPRIGHT

- K-Factor = 5.6 (80)
- **SIN RA6424**
- See Bulletin 064
- Stainless Steel

F1-80SS UPRIGHT

- K-Factor = 8.0 (115)
- **SIN RA6422**
- See Bulletin 064
- Stainless Steel

| Part Number | Short Code | Temperature | | Finish | List Price |
|--|------------|-------------|-------|-----------------|------------|
| MODEL F156-SS PENDENT K5.6 (80) THREADS 1/2" (15MM) RA6414 | | | | | |
| A213103299 | F56P0SS | 135°F | 57°C | Stainless Steel | £ 594.38 |
| A215103299 | F56P1SS | 155°F | 68°C | Stainless Steel | £ Call |
| A217103299 | F56P5SS | 175°F | 79°C | Stainless Steel | £ 594.38 |
| A220103299 | F56P2SS | 200°F | 93°C | Stainless Steel | £ 594.38 |
| A228103299 | F56P3SS | 286°F | 141°C | Stainless Steel | £ 594.38 |
| A236103299 | F56P6SS | 360°F | 182°C | Stainless Steel | £ 594.38 |
| A250103299 | F56P7SS | 500°F | 260°C | Stainless Steel | £ 594.38 |
| MODEL F180-SS PENDENT K8.0 (115) THREADS 3/4" (20MM) RA6412 | | | | | |
| A213103498 | FP0LSS | 135°F | 57°C | Stainless Steel | £ 627.39 |
| A215103498 | FP1LSS | 155°F | 68°C | Stainless Steel | £ 627.39 |
| A217103498 | FP5LSS | 175°F | 79°C | Stainless Steel | £ 627.39 |
| A220103498 | FP2LSS | 200°F | 93°C | Stainless Steel | £ 627.39 |
| A228103498 | FP3LSS | 286°F | 141°C | Stainless Steel | £ 627.39 |
| A236103498 | FP6LSS | 360°F | 182°C | Stainless Steel | £ 627.39 |
| MODEL F156-SS UPRIGHT K5.6 (80) THREADS 1/2" (15MM) RA6424 | | | | | |
| AA131032R9 | F56U0SS | 135°F | 57°C | Stainless Steel | £ 594.38 |
| AA151032R9 | F56U1SS | 155°F | 68°C | Stainless Steel | £ 594.38 |
| AA171032R9 | F56U5SS | 175°F | 79°C | Stainless Steel | £ 594.38 |
| AA201032R9 | F56U2SS | 200°F | 93°C | Stainless Steel | £ 594.38 |
| AA281032R9 | F56U3SS | 286°F | 141°C | Stainless Steel | £ 594.38 |
| AA361032R9 | F56U6SS | 360°F | 182°C | Stainless Steel | £ 594.38 |
| AA501032R9 | F56U7SS | 500°F | 260°C | Stainless Steel | £ 594.38 |
| MODEL F180-SS UPRIGHT K8.0 (115) THREADS 3/4" (20MM) RA6422 | | | | | |
| A113103498 | FU0LSS | 135°F | 57°C | Stainless Steel | £ 627.39 |
| A115103498 | FU1LSS | 155°F | 68°C | Stainless Steel | £ 627.39 |
| A117103498 | FU5LSS | 175°F | 79°C | Stainless Steel | £ 627.39 |
| A120103498 | FU2LSS | 200°F | 93°C | Stainless Steel | £ 627.39 |
| A128103498 | FU3LSS | 286°F | 141°C | Stainless Steel | £ 627.39 |
| A136103498 | FU6LSS | 360°F | 182°C | Stainless Steel | £ 627.39 |
| MODEL F1 RECESSED ESCUTCHEONS & COLLAR ASSEMBLY | | | | | |
| 6800610010 | GF1SS | 1/2" (15mm) | | Stainless Steel | £ 66.59 |
| 6800970010 | GF1LSS | 3/4" (20mm) | | Stainless Steel | £ 66.59 |
| MODEL FP PUSH-ON / THREAD-OFF ESCUTCHEONS | | | | | |
| 6801411000 | FPSS | 1/2" (15mm) | | Stainless Steel | £ 99.89 |
| 6801401000 | FPLSS | 3/4" (20mm) | | Stainless Steel | £ 99.89 |
| MODEL B ONE PIECE ESCUTCHEONS | | | | | |
| 6800121002 | BSS | 1/2" (15mm) | | Stainless Steel | £ 39.97 |
| 6800091002 | BLSS | 3/4" (20mm) | | Stainless Steel | £ 39.97 |

| | | | | | |
|------------|-----|-----------------------------------|--|--|----------|
| 6880050100 | WW2 | Wrench, W2, Pendent, Upright, HSW | | | £ 114.28 |
| 6880100120 | WW4 | Wrench, W4, Recessed, Concealed | | | £ 339.15 |



F156-300 UPRIGHT

- K-Factor = 5.6 (80)
- **SIN RA2525**
- See Bulletin 025
- 300 PSI



F180-300 UPRIGHT

- K-Factor = 8.0 (115)
- **SIN RA7622**
- See Bulletin 076
- 300 PSI

| Part Number | Short Code | Temperature | | Finish | List Price |
|---|------------|-------------|-------|------------|------------|
| MODEL F156 UPRIGHT K5.6 (80) THREADS 1/2" (15MM) RA2525 300PSI | | | | | |
| AF131132R9 | F56U0B3 | 135°F | 57°C | Brass | £ 29.57 |
| AF132132R9 | F56U0C3 | 135°F | 57°C | Chrome | £ 35.82 |
| AF138732R9 | F56U0W3 | 135°F | 57°C | White | £ 40.82 |
| AF151132S9 | F56U1B3N | 155°F | 68°C | Brass | £ 29.57 |
| AF152132S9 | F56U1C3N | 155°F | 68°C | Chrome | £ 35.82 |
| AF158732S9 | F56U1W3N | 155°F | 68°C | Poly White | £ 41.18 |
| AF171132S9 | F56U5B3N | 175°F | 79°C | Brass | £ 29.57 |
| AF172132R9 | F56U5C3 | 175°F | 79°C | Chrome | £ Call |
| AF178732R9 | F56U5W3 | 175°F | 79°C | Poly White | £ 41.18 |
| AF201132S9 | F56U2B3N | 200°F | 93°C | Brass | £ 29.57 |
| AF202132S9 | F56U2C3N | 200°F | 93°C | Chrome | £ 35.82 |
| | | °F | °C | | £ Call |
| AF281132S9 | F56U3B3N | 286°F | 141°C | Brass | £ 29.57 |
| AF282132S9 | F56U3C3N | 286°F | 141°C | Chrome | £ 35.82 |
| AF288732S9 | F56U3W3N | 286°F | 141°C | Poly White | £ 41.18 |
| MODEL F1 LO UPRIGHT K8.0 (115) THREADS 3/4" (20MM) RA7622 300PSI | | | | | |
| AF13113498 | FU0LB3 | 135°F | 57°C | Brass | £ 36.07 |
| AF13213498 | FU0LC3 | 135°F | 57°C | Chrome | £ 44.42 |
| AF13873498 | FU0LW3 | 135°F | 57°C | White | £ 49.56 |
| AF151134S8 | FU1LB3N | 155°F | 68°C | Brass | £ 35.73 |
| AF152134S8 | FU1LC3N | 155°F | 68°C | Brass | £ 44.42 |
| AF15873498 | FU1LW3 | 155°F | 68°C | Poly White | £ 50.94 |
| AF171134S8 | FU5LB3N | 175°F | 79°C | Brass | £ 35.73 |
| AF17213498 | FU5LC3 | 175°F | 79°C | Chrome | £ 44.42 |
| AF17873498 | FU5LW3 | 175°F | 79°C | White | £ 49.56 |
| AF201134S8 | FU2LB3N | 200°F | 93°C | Brass | £ 35.73 |
| AF20213498 | FU2LC3 | 200°F | 93°C | Chrome | £ 44.42 |
| AF20873498 | FU2LW3 | 200°F | 93°C | Poly White | £ 50.94 |
| AF281134S8 | FU3LB3N | 286°F | 141°C | Brass | £ 35.73 |
| AF28213498 | FU3LC3 | 286°F | 141°C | Chrome | £ 44.42 |
| AF28873498 | FU3LW3 | 286°F | 141°C | White | £ 49.56 |
| AF36113498 | FU6LB3 | 360°F | 182°C | Brass | £ 40.47 |
| AF36213498 | FU6LC3 | 360°F | 182°C | Chrome | £ 48.07 |
| AF36873498 | FU6LW3 | 360°F | 182°C | White | £ 53.67 |

6880050100 WW2 Wrench, W2, Pendent, Upright, HSW £ 114.28



F156

- K-Factor = 80 (5.6)
- **SIN RA1314**
- See Bulletin 013

| Part Number | Short Code | Temperature | | Finish | List Price |
|---|------------|-------------|-------|------------|------------|
| MODEL F156 PENDENT K5.6 (80) THREADS 1/2" (15MM) RA1314 | | | | | |
| A213113299 | F56P0B | 135°F | 57°C | Brass | £ 26.96 |
| A213213299 | F56P0C | 135°F | 57°C | Chrome | £ Call |
| A213873299 | F56P0W | 135°F | 57°C | White | £ Call |
| A215113299 | F56P1B | 155°F | 68°C | Brass | £ Call |
| A215213299 | F56P1C | 155°F | 68°C | Chrome | £ Call |
| A215873299 | F56P1W | 155°F | 68°C | Poly White | £ 37.99 |
| A217113299 | F56P5B | 175°F | 79°C | Brass | £ 26.96 |
| A217213299 | F56P5C | 175°F | 79°C | Chrome | £ 31.92 |
| A217873299 | F56P5W | 175°F | 79°C | Poly White | £ 37.99 |
| A220113299 | F56P2B | 200°F | 93°C | Brass | £ 26.96 |
| A220213299 | F56P2C | 200°F | 93°C | Chrome | £ 31.92 |
| A220873299 | F56P2W | 200°F | 93°C | White | £ 37.99 |
| A228113299 | F56P3B | 286°F | 141°C | Brass | £ 26.96 |
| A228213299 | F56P3C | 286°F | 141°C | Chrome | £ 31.92 |
| A228873299 | F56P3W | 286°F | 141°C | Poly White | £ 37.99 |
| A236113299 | F56P6B | 360°F | 182°C | Brass | £ 30.32 |
| A236213299 | F56P6C | 360°F | 182°C | Chrome | £ 35.07 |
| | | °F | °C | | £ Call |
| MODEL F156 PENDENT K5.6 (80) BSPT THREADS 1/2" (15MM) RA1314 | | | | | |
| A213113292 | F56P0BM | 135°F | 57°C | Brass | £ 26.96 |
| A213213292 | F56P0CM | 135°F | 57°C | Chrome | £ 31.92 |
| A213873292 | F56P0WM | 135°F | 57°C | Poly White | £ 37.99 |
| A215113292 | F56P1BM | 155°F | 68°C | Brass | £ 26.96 |
| A215213292 | F56P1CM | 155°F | 68°C | Chrome | £ 31.92 |
| A215873292 | F56P1WM | 155°F | 68°C | Poly White | £ 37.99 |
| A217113292 | F56P5BM | 175°F | 79°C | Brass | £ 26.96 |
| A217213292 | F56P5CM | 175°F | 79°C | Chrome | £ 31.92 |
| A217873292 | F56P5WM | 175°F | 79°C | Poly White | £ 37.99 |
| A220113292 | F56P2BM | 200°F | 93°C | Brass | £ 26.96 |
| A220213292 | F56P2CM | 200°F | 93°C | Chrome | £ 31.92 |
| A220873292 | F56P2WM | 200°F | 93°C | Poly White | £ 37.99 |
| A228113292 | F56P3BM | 286°F | 141°C | Brass | £ 26.96 |
| A228213292 | F56P3CM | 286°F | 141°C | Chrome | £ 31.92 |
| A228873292 | F56P3WM | 360°F | 182°C | White | £ 37.99 |
| A236113292 | F56P3BM | 360°F | 182°C | Brass | £ 30.32 |
| A236213292 | F56P6CM | 360°F | 182°C | Chrome | £ 35.07 |
| A236873292 | F56P6WM | 360°F | 182°C | White | £ 41.30 |

6880050100 WW2 Requires Model W2 Sprinkler Wrench £ 114.28



F1 LO

- K-Factor = 115 (8.0)
- SIN R1712
- See Bulletin 117

| Part Number | Short Code | Temperature | | Finish | List Price |
|--|------------|-------------|-------|------------|------------|
| MODEL F1 LO PENDENT K8.0 (115) THREADS 3/4" (20MM) R1712 | | | | | |
| A213113498 | FP0LB | 135°F | 57°C | Brass | £ 34.14 |
| A213213498 | FP0LC | 135°F | 57°C | Chrome | £ 41.18 |
| A213873498 | FP0LW | 135°F | 57°C | White | £ 49.20 |
| A215113498 | FP1LB | 155°F | 68°C | Brass | £ 34.14 |
| A215213498 | FP1LC | 155°F | 68°C | Chrome | £ 41.18 |
| A215873498 | FP1LW | 155°F | 68°C | White | £ 49.20 |
| A217113498 | FP5LB | 175°F | 79°C | Brass | £ 34.14 |
| A217213498 | FP5LC | 175°F | 79°C | Chrome | £ 41.18 |
| A217873498 | FP5LW | 175°F | 79°C | White | £ 49.20 |
| A220113498 | FP2LB | 200°F | 93°C | Brass | £ 34.14 |
| A220213498 | FP2LC | 200°F | 93°C | Chrome | £ 41.18 |
| A220873498 | FP2LW | 200°F | 93°C | Poly White | £ 49.20 |
| A228113498 | FP3LB | 286°F | 141°C | Brass | £ 34.14 |
| A228213498 | FP3LC | 286°F | 141°C | Chrome | £ 41.18 |
| A228873498 | FP3LW | 286°F | 141°C | White | £ 49.20 |
| A236113498 | FP6LB | 360°F | 182°C | Brass | £ 34.14 |
| A236213498 | FP6LC | 360°F | 182°C | Chrome | £ 41.18 |
| A236873498 | FP6LW | 360°F | 182°C | White | £ 49.20 |
| MODEL F1 LO PENDENT K8.0 (115) BSPT THREADS 3/4" (20MM) R1712 | | | | | |
| A213113495 | FP0LBM | 135°F | 57°C | Brass | £ 34.14 |
| A213213495 | FP0LCM | 135°F | 57°C | Chrome | £ 41.18 |
| A213873495 | FP0LWM | 135°F | 57°C | White | £ 49.20 |
| A215113495 | FP1LBM | 155°F | 68°C | Brass | £ 34.14 |
| A215213495 | FP1LCM | 155°F | 68°C | Chrome | £ 41.18 |
| A215873495 | FP1LWM | 155°F | 68°C | White | £ 49.20 |
| A217113495 | FP5LBM | 175°F | 79°C | Brass | £ 34.14 |
| A217213495 | FP5LCM | 175°F | 79°C | Chrome | £ 41.18 |
| A217873495 | FP5LWM | 175°F | 79°C | Poly White | £ 49.20 |
| A220113495 | FP2LBM | 200°F | 93°C | Brass | £ 34.14 |
| A220213495 | FP2LCM | 200°F | 93°C | Chrome | £ 41.18 |
| A220873495 | FP2LWM | 200°F | 93°C | White | £ 49.20 |
| A228113495 | FP3LBM | 286°F | 141°C | Brass | £ 34.14 |
| A228213495 | FP3LCM | 286°F | 141°C | Chrome | £ 41.18 |
| A228873495 | FP3LWM | 286°F | 141°C | Poly White | £ 49.20 |
| A236113495 | FP6LBM | 360°F | 182°C | Brass | £ 34.14 |
| A236213495 | FP6LCM | 360°F | 182°C | Chrome | £ 41.18 |
| A236873495 | FP6LWM | 360°F | 182°C | Poly White | £ 49.20 |

6880050100 WW2 Requires Model W2 Sprinkler Wrench £ 114.28




F1 28 PENDENT

- K-Factor = 2.8 (40)
- **SIN RA1311**
- See Bulletin 066



F1 42 PENDENT

- K-Factor = 4.2 (60)
- **SIN RA1313**
- See Bulletin 067



| Part Number | Short Code | Temperature | | Finish | List Price |
|---|------------|-----------------------|-------|------------|------------|
| MODEL F128 PENDENT K 2.8 (40) THREADS 1/2" (15MM) RA1311 | | | | | |
| AB151124S9 | F28P1BN | 155°F | 68°C | Brass | £ 40.78 |
| AB152124S9 | F28P1CN | 155°F | 68°C | Chrome | £ 48.02 |
| AB158724S9 | F28P1WN | 155°F | 68°C | Poly White | £ 51.60 |
| AB172124S9 | F28P5CN | 175°F | 79°C | Chrome | £ 48.02 |
| AB178724S9 | F28P5WN | 175°F | 79°C | Poly White | £ 51.60 |
| AB201124S9 | F28P2BN | 200°F | 93°C | Brass | £ 40.78 |
| AB202124S9 | F28P2CN | 200°F | 93°C | Chrome | £ 48.02 |
| AB208724S9 | F28P2WN | 200°F | 93°C | Poly White | £ 51.60 |
| AB281124S9 | F28P3BN | 286°F | 141°C | Brass | £ 40.78 |
| AB282124S9 | F28P3CN | 286°F | 141°C | Chrome | £ 48.02 |
| AB288724S9 | F28P3WN | 286°F | 141°C | Poly White | £ 51.60 |
| MODEL F142 PENDENT K4.2 (60) THREADS 1/2" (15MM) RA1313 | | | | | |
| AB131128S9 | F42P0BN | 135°F | 57°C | Brass | £ 40.78 |
| AB132128S9 | F42POCN | 135°F | 57°C | Chrome | £ 48.02 |
| AB138728S9 | F42POWN | 135°F | 57°C | White | £ 51.60 |
| AB151128S9 | F42P1BN | 155°F | 68°C | Brass | £ 40.78 |
| AB152128S9 | F42P1CN | 155°F | 68°C | Chrome | £ 48.02 |
| AB171128S9 | | 175°F | 79°C | Brass | £ 40.78 |
| | | °F | °C | | £ Call |
| AB178728S9 | F42P5WN | 175°F | 79°C | Poly White | £ 51.60 |
| AB201128R9 | F42P2B | 200°F | 93°C | Brass | £ Call |
| AB202128S9 | F42P2CN | 200°F | 93°C | Chrome | £ 48.02 |
| AB208728S9 | F42P2WN | 200°F | 93°C | White | £ 51.60 |
| AB361128S9 | F42P6BN | 360°F | 182°C | Brass | £ 44.05 |
| AB362128S9 | F42P6CN | 360°F | 182°C | Chrome | £ 51.32 |
| AB368728S9 | F42P6WN | 360°F | 182°C | White | £ 55.26 |
| MODEL F1 RECESSED ESCUTCHEONS & COLLAR ASSEMBLY | | | | | |
| 6800630001 | GF1B | 1/2" (15mm) | | Brass | £ 20.97 |
| 6800600001 | GF1C | 1/2" (15mm) | | Chrome | £ 11.30 |
| 6800640001 | GF1W | 1/2" (15mm) | | White | £ 11.30 |
| MODEL F2 RECESSED ESCUTCHEONS & COLLAR ASSEMBLY | | | | | |
| 6800830000 | GF2B | 1/2" (15mm) | | Brass | £ 20.97 |
| 6800800000 | GF2C | 1/2" (15mm) | | Chrome | £ 11.30 |
| 6800840000 | GF2W | 1/2" (15mm) | | White | £ 11.30 |
| MODEL FP PUSH-ON/THREAD-OFF ESCUTCHEONS | | | | | |
| 6801412100 | FPC | FP PUSH-ON/THREAD-OFF | | Chrome | £ 21.81 |
| 6801417200 | FPW | FP PUSH-ON/THREAD-OFF | | White | £ 21.81 |

| | | | | |
|------------|-----|-----------------------------------|--|----------|
| 6880050100 | WW2 | Wrench, W2, Pendent, Upright, HSW | | £ 114.28 |
| 6880100120 | WW4 | Wrench, W4, Recessed, Concealed | | £ 339.15 |



F156-300

- K-Factor = 5.6 (80)
- **SIN RA2514**
- See Bulletin 075
- **300 PSI**



F1-300

- K-Factor = 8.0 (115)
- **SIN R5512**
- See Bulletin 076
- **300 PSI**

| Part Number | Short Code | Temperature | | Finish | List Price |
|--|------------|-------------|-------|------------|------------|
| MODEL F156 PENDENT K5.6 (80) THREADS 1/2" (15MM) RA2514 300 PSI | | | | | |
| AG131132S9 | F56P0B3N | 135°F | 57°C | Brass | £ 29.57 |
| AG132132S9 | F56P0C3N | 135°F | 57°C | Chrome | £ 34.77 |
| AG138732S9 | F56P0W3N | 135°F | 57°C | Poly White | £ 40.02 |
| AG151132S9 | F56P1B3N | 155°F | 68°C | Brass | £ 29.57 |
| AG152132S9 | F56P1C3N | 155°F | 68°C | Chrome | £ 34.77 |
| AG158732S9 | F56P1W3N | 155°F | 68°C | Poly White | £ 40.02 |
| AG171132S9 | F56P5B3N | 175°F | 79°C | Brass | £ 29.57 |
| AG172132S9 | F56P5C3N | 175°F | 79°C | Chrome | £ 34.77 |
| AG178732S9 | F56P5W3N | 175°F | 79°C | Poly White | £ 39.95 |
| AG201132S9 | F56P2B3N | 200°F | 93°C | Brass | £ 29.57 |
| AG202132S9 | F56P2C3N | 200°F | 93°C | Chrome | £ 34.77 |
| AG208732S9 | F56P2W3N | 200°F | 93°C | Poly White | £ 40.02 |
| AG281132S9 | F56P3B3N | 286°F | 141°C | Brass | £ 34.77 |
| AG282132S9 | F56P3C3N | 286°F | 141°C | Chrome | £ 34.77 |
| AG288732S9 | F56P3W3N | 286°F | 141°C | Poly White | £ 40.02 |
| AG361132S9 | F56P6B3N | 360°F | 182°C | Brass | £ 29.57 |
| AG362132S9 | F56P6C3N | 360°F | 182°C | Chrome | £ 37.97 |
| AG368732S9 | F56P6W3N | 360°F | 182°C | White | £ 43.25 |
| MODEL F180 PENDENT K8.0 (115) THREADS 3/4" (20MM) R5512 300 PSI | | | | | |
| AG13113498 | FP0LB3 | 135°F | 57°C | Brass | £ 37.17 |
| AG13213498 | FP0LC3 | 135°F | 57°C | Chrome | £ 44.42 |
| AG13873498 | FP0LW3 | 135°F | 57°C | White | £ 50.02 |
| AG151134S8 | FP1LB3N | 155°F | 68°C | Brass | £ 37.17 |
| AG152134S8 | FP1LC3N | 155°F | 68°C | Chrome | £ 44.42 |
| AG158734S8 | FP1LW3N | 155°F | 68°C | Poly White | £ 52.84 |
| AG17113498 | FP5LB3 | 175°F | 79°C | Brass | £ 37.17 |
| AG17213498 | FP5LC3 | 175°F | 79°C | Chrome | £ 44.42 |
| AG17873498 | FP5LW3 | 175°F | 79°C | White | £ 50.02 |
| AG20113498 | FP2LB3 | 200°F | 93°C | Brass | £ 37.17 |
| AG20213498 | FP2LC3 | 200°F | 93°C | Chrome | £ 44.42 |
| AG20873498 | FP2LW3 | 200°F | 93°C | Poly White | £ 52.84 |
| AG28113498 | FP3LB3 | 286°F | 141°C | Brass | £ 37.17 |
| AG28213498 | FP3LC3 | 286°F | 141°C | Chrome | £ 44.42 |
| AG28873498 | FP3LW3 | 286°F | 141°C | White | £ 52.84 |
| AG36113498 | FP6LB3 | 360°F | 182°C | Brass | £ 40.47 |
| AG36213498 | FP6LC3 | 360°F | 182°C | Chrome | £ 48.07 |
| AG36873498 | FP6LW3 | 360°F | 182°C | White | £ 53.67 |

6880050100 WW2 Wrench, W2, Pendent, Upright, HSW £ 114.28



F1 56

- K-Factor = 5.6 (80)
- **SIN RA1375**
- See Bulletin 013



F1 LO

- K-Factor = 8.0 (115)
- **SIN R1772**
- See Bulletin 117

| Part Number | Short Code | Temperature | | Finish | List Price |
|--|------------|-------------|-------|------------|------------|
| MODEL F156 CONVENTIONAL K 5.6 (80) THREADS 1/2" (15MM) RA1375 | | | | | |
| AC131132S9 | F56C0BN | 135°F | 57°C | Brass | £ 26.96 |
| AC132132S9 | F56C0CN | 135°F | 57°C | Chrome | £ 31.92 |
| AC138732S9 | F56C0WN | 135°F | 57°C | Poly White | £ 37.99 |
| AC151132S9 | F56C1BN | 155°F | 68°C | Brass | £ 26.96 |
| AC152132S9 | F56C1CN | 155°F | 68°C | Chrome | £ 31.92 |
| AC158732S9 | F56C1WN | 155°F | 68°C | Poly White | £ 37.99 |
| AC171132S9 | F56C5BN | 175°F | 79°C | Brass | £ 26.96 |
| AC172132S9 | F56C5CN | 175°F | 79°C | Chrome | £ 31.92 |
| AC178732S9 | F56C5WN | 175°F | 79°C | Poly White | £ 37.99 |
| AC201132S9 | F56C2BN | 200°F | 93°C | Brass | £ 26.96 |
| AC202132S9 | F56C2CN | 200°F | 93°C | Chrome | £ 31.92 |
| AC208732S9 | F56C2WN | 200°F | 93°C | Poly White | £ 37.99 |
| AC281132S9 | F56C3BN | 286°F | 141°C | Brass | £ 26.96 |
| AC282132S9 | F56C3CN | 286°F | 141°C | Chrome | £ 31.92 |
| AC288732S9 | F56C3WN | 286°F | 141°C | Poly White | £ 37.99 |
| AC361132S9 | F56C6BN | 360°F | 182°C | Brass | £ 26.96 |
| AC362132S9 | F56C6CN | 360°F | 182°C | Chrome | £ 31.92 |
| AC368732S9 | F56C6WN | 360°F | 182°C | Poly White | £ 37.99 |
| MODEL F1-80 CONVENTIONAL K8.0 (115) THREADS 3/4" (20MM) R1772 | | | | | |
| A313113498 | FC0LB | 135°F | 57°C | Brass | £ 34.14 |
| A313213498 | FC0LC | 135°F | 57°C | Chrome | £ 41.18 |
| A313873498 | FC0LW | 135°F | 57°C | White | £ 49.20 |
| A315113498 | FC1LB | 155°F | 68°C | Brass | £ 34.14 |
| A315213498 | FC1LC | 155°F | 68°C | Chrome | £ 41.18 |
| A315873498 | FC1LW | 155°F | 68°C | White | £ 49.20 |
| A317113498 | FC5LB | 175°F | 79°C | Brass | £ 34.14 |
| A317213498 | FC5LC | 175°F | 79°C | Chrome | £ 41.18 |
| A320113498 | FC2LB | 200°F | 93°C | Brass | £ 34.14 |
| A320213498 | FC2LC | 200°F | 93°C | Chrome | £ 41.18 |
| A320873498 | FC2LW | 200°F | 93°C | White | £ 49.20 |
| A328113498 | FC3LB | 286°F | 141°C | Brass | £ 34.14 |
| A328213498 | FC3LC | 286°F | 141°C | Chrome | £ 41.18 |
| A328873498 | FC3LW | 286°F | 141°C | White | £ 49.20 |

6880050100 WW2 Wrench, W2, Pendent, Upright, HSW £ 114.28



F1 56

- K-Factor = 80 (5.6)
- **SIN RA1375**
- See Bulletin 013

| Part Number | Short Code | Temperature | | Finish | List Price |
|---|------------|-------------|-------|------------|------------|
| MODEL F156 CONVENTIONAL K 5.6 (80) THREADS 1/2" (15MM) RA1375 | | | | | |
| AC131132R9 | F56C0B | 135°F | 57°C | Brass | £ Call |
| AC132132R9 | F56C0C | 135°F | 57°C | Chrome | £ Call |
| AC138732R9 | F56C0W | 135°F | 57°C | Poly White | £ Call |
| AC151132R9 | F56C1B | 155°F | 68°C | Brass | £ Call |
| AC152132R9 | F56C1C | 155°F | 68°C | Chrome | £ Call |
| AC158732R9 | F56C1W | 155°F | 68°C | White | £ Call |
| AC171132R9 | F56C5B | 175°F | 79°C | Brass | £ Call |
| AC172132R9 | F56C5C | 175°F | 79°C | Chrome | £ Call |
| AC178732R9 | F56C5W | 175°F | 79°C | Poly White | £ 37.99 |
| AC201132R9 | F56C2B | 200°F | 93°C | Brass | £ Call |
| AC202132R9 | F56C2C | 200°F | 93°C | Chrome | £ Call |
| AC208732R9 | F56C2W | 200°F | 93°C | Poly White | £ Call |
| AC281132R9 | F56C3B | 286°F | 141°C | Brass | £ Call |
| AC282132R9 | F56C3C | 286°F | 141°C | Chrome | £ Call |
| | | °F | °C | | £ Call |
| | | °F | °C | | £ Call |
| AC362132R9 | F56C6C | 360°F | 182°C | Chrome | £ Call |
| | | °F | °C | | £ Call |
| MODEL F156 CONVENTIONAL K 5.6 (80) BSPT THREADS 1/2" (15MM) RA1375 | | | | | |
| AC131132R2 | F56C0BM | 135°F | 57°C | Brass | £ 26.96 |
| AC132132R2 | F56C0CM | 135°F | 57°C | Chrome | £ 31.92 |
| AC138732R2 | F56C0WM | 135°F | 57°C | White | £ 37.99 |
| AC151132R2 | F56C1BM | 155°F | 68°C | Brass | £ 26.96 |
| AC152132R2 | F56C1CM | 155°F | 68°C | Chrome | £ 31.92 |
| AC158732R2 | F56C1WM | 155°F | 68°C | Poly White | £ 37.99 |
| | | °F | °C | | £ Call |
| AC172132R2 | F56C5CM | 175°F | 79°C | Chrome | £ 31.92 |
| AC178732R2 | F56C5WM | 175°F | 79°C | White | £ 37.99 |
| AC201132R2 | F56C2BM | 200°F | 93°C | Brass | £ 26.96 |
| AC202132R2 | F56C2CM | 200°F | 93°C | Chrome | £ 31.92 |
| AC208732R2 | F56C2WM | 200°F | 93°C | Poly White | £ 37.99 |
| AC281132R2 | F56C3BM | 286°F | 141°C | Brass | £ 26.96 |
| AC282132R2 | F56C3CM | 286°F | 141°C | Chrome | £ 31.92 |
| | | °F | °C | | £ Call |

6880050100 WW2 Requires Model W2 Sprinkler Wrench £ 114.28



F1 LO

- Conventional
- **SIN R1772**
- See Bulletin 117

| Part Number | Short Code | Temperature | | Finish | List Price |
|---|------------|-------------|-------|------------|------------|
| MODEL F1 LO CONVENTIONAL K8.0 (115) THREADS 3/4" (20MM) R1772 | | | | | |
| A313113498 | FC0LB | 135°F | 57°C | Brass | £ 34.14 |
| A313213498 | FC0LC | 135°F | 57°C | Chrome | £ 41.18 |
| A313873498 | FC0LW | 135°F | 57°C | White | £ 49.20 |
| A315113498 | FC1LB | 155°F | 68°C | Brass | £ 34.14 |
| A315213498 | FC1LC | 155°F | 68°C | Chrome | £ 41.18 |
| A315873498 | FC1LW | 155°F | 68°C | White | £ 49.20 |
| A317113498 | FC5LB | 175°F | 79°C | Brass | £ 34.14 |
| A317213498 | FC5LC | 175°F | 79°C | Chrome | £ 41.18 |
| | | °F | °C | | £ Call |
| A320113498 | FC2LB | 200°F | 93°C | Brass | £ 34.14 |
| A320213498 | FC2LC | 200°F | 93°C | Chrome | £ 41.18 |
| A320873498 | FC2LW | 200°F | 93°C | White | £ 49.20 |
| A328113498 | FC3LB | 286°F | 141°C | Brass | £ 34.14 |
| A328213498 | FC3LC | 286°F | 141°C | Chrome | £ 41.18 |
| A328873498 | FC3LW | 286°F | 141°C | White | £ 49.20 |
| MODEL F1 LO CONVENTIONAL K8.0 (115) BSPT THREADS 3/4" (20MM) R1772 | | | | | |
| A313113495 | FC0LBM | 135°F | 57°C | Brass | £ 34.14 |
| A313213495 | FC0LCM | 135°F | 57°C | Chrome | £ 41.18 |
| A313873495 | FC0LWM | 135°F | 57°C | White | £ 49.20 |
| A315113495 | FC1LBM | 155°F | 68°C | Brass | £ 34.14 |
| A315213495 | FC1LCM | 155°F | 68°C | Chrome | £ 42.73 |
| A315873495 | FC1LWM | 155°F | 68°C | White | £ 49.20 |
| A317113495 | FC5LBM | 175°F | 79°C | Brass | £ 34.14 |
| A317213495 | FC5LCM | °F | °C | | £ 41.18 |
| A317873495 | FC5LWM | °F | °C | | £ 49.20 |
| A320113495 | FC2LBM | 200°F | 93°C | Brass | £ 34.14 |
| A320213495 | FC2LCM | °F | °C | | £ 41.18 |
| A320873495 | EC2LWM | °F | °C | | £ 49.20 |
| A328113495 | FC3LBM | 286°F | 141°C | Brass | £ 34.14 |
| A328213495 | FC3LCM | 286°F | 141°C | Chrome | £ 41.18 |
| A328873495 | FC3LWM | 286°F | 141°C | Poly White | £ 49.20 |

6880050100 WW2 Requires Model W2 Sprinkler Wrench £ 114.28



F1 56 HSW

- K-Factor = 80 (5.6)
- **SIN RA1375**
- See Bulletin 013

| Part Number | Short Code | Temperature | | Finish | List Price |
|--|------------|-------------|-------|------------|------------|
| MODEL F156 HORIZONTAL K5.6 (80) THREADS 1/2" (15MM) RA1335 | | | | | |
| AD131132R9 | F56H0B | 135°F | 57°C | Brass | £ Call |
| AD132132R9 | F56H0C | 135°F | 57°C | Chrome | £ Call |
| AD138732R9 | F56H0W | 135°F | 57°C | Poly White | £ Call |
| AD151132R9 | F56H1B | 155°F | 68°C | Brass | £ Call |
| AD152132R9 | F56H1C | 155°F | 68°C | Chrome | £ Call |
| AD158732R9 | F56H1W | 155°F | 68°C | White | £ Call |
| AD171132R9 | F56H5B | 175°F | 79°C | Brass | £ Call |
| AD172132R9 | F56H5C | 175°F | 79°C | Chrome | £ Call |
| AD178732R9 | F56H5W | 175°F | 79°C | Poly White | £ Call |
| AD201132R9 | F56H2B | 200°F | 93°C | Brass | £ Call |
| AD202132R9 | F56H2C | 200°F | 93°C | Chrome | £ Call |
| | | °F | °C | | £ Call |
| AD281132R9 | F56H3B | 286°F | 141°C | Brass | £ Call |
| AD282132R9 | F56H3C | 286°F | 141°C | Chrome | £ Call |
| AD288732R9 | F56H3W | 286°F | 141°C | Poly White | £ Call |
| AD361132R9 | F56H6B | 360°F | 182°C | Brass | £ Call |
| AD362132R9 | F56H6C | 360°F | 182°C | Chrome | £ Call |
| AD368732R9 | F56H6W | 360°F | 182°C | Poly White | £ Call |
| MODEL F156 HORIZONTAL K5.6 (80) BSPT THREADS 1/2" (15MM) RA1335 | | | | | |
| AD131132R2 | F56H0BM | 135°F | 57°C | Brass | £ 41.92 |
| AD132132R2 | F56H0CM | 135°F | 57°C | Chrome | £ 48.02 |
| AD138732R2 | F56H0WM | 135°F | 57°C | Poly White | £ 51.55 |
| AD151132R2 | F56H1BM | 155°F | 68°C | Brass | £ 41.92 |
| AD152132R2 | F56H1CM | 155°F | 68°C | Chrome | £ 48.02 |
| AD158732R2 | F56H1WM | 155°F | 68°C | Poly White | £ 51.55 |
| AD171132R2 | F56H5BM | 175°F | 79°C | Brass | £ 41.92 |
| AD172132R2 | F56H5CM | 175°F | 79°C | Bronze | £ 48.02 |
| AD178732R2 | F56H5WM | 175°F | 79°C | Bronze | £ 51.55 |
| AD201132R2 | F56H2BM | 200°F | 93°C | Brass | £ 41.92 |
| AD202132R2 | F56H2CM | 200°F | 93°C | Chrome | £ 48.02 |
| AD208732R2 | F56H2WM | 200°F | 93°C | White | £ 51.55 |
| AD281132R2 | F56H3BM | 286°F | 141°C | Brass | £ 41.92 |
| AD282132R2 | F56H3CM | 286°F | 141°C | Chrome | £ 48.02 |
| AD288732R2 | F56H3WM | 286°F | 141°C | Poly White | £ 51.55 |
| AD361132R2 | F56H6BM | 360°F | 182°C | Brass | £ 41.92 |
| AD362132R2 | F56H6CM | 360°F | 182°C | Chrome | £ 48.02 |
| AD368732R2 | F56H6WM | 360°F | 182°C | White | £ 51.55 |
| MODEL F1 RECESSED ESCUTCHEONS & COLLAR ASSEMBLY | | | | | |
| 6800630001 | GF1B | 1/2" (15MM) | | Brass | £ 20.97 |
| 6800600001 | GF1C | 1/2" (15MM) | | Chrome | £ 11.30 |
| 6800640001 | GF1W | 1/2" (15MM) | | White | £ 11.30 |

| | | | |
|------------|------|------------------------------------|----------|
| 6880050100 | WW2 | Requires Model W2 Sprinkler Wrench | £ 114.28 |
| 6880060000 | WGFR | For Recessed Use Model GFR2 Wrench | £ 339.15 |



F1 56

- K-Factor = 5.6 (80)
- Vertical Sidewall
- **SIN RA1385**
- See Bulletin 013

| Part Number | Short Code | Temperature | | Finish | List Price |
|--|------------|-------------|-------|------------|------------|
| MODEL F156 VERTICAL K5.6 (80) THREADS 1/2" (15MM) RA1385 | | | | | |
| | | °F | °C | | £ Call |
| AE132132R9 | F56V0C | 135°F | 57°C | Chrome | £ Call |
| AE138732R9 | F56V0W | 135°F | 57°C | White | £ 53.95 |
| AE151132R9 | F56V1B | 155°F | 68°C | Brass | £ Call |
| AE152132R9 | F56V1C | 155°F | 68°C | Chrome | £ Call |
| AE158732R9 | F56V1W | 155°F | 68°C | Poly White | £ Call |
| | | °F | °C | | £ Call |
| AE172132R9 | F56V5C | 175°F | 79°C | Chrome | £ Call |
| AE178732R9 | F56V5W | 175°F | 79°C | Poly White | £ Call |
| | | °F | °C | | £ Call |
| AE202132R9 | F56V2C | 200°F | 93°C | Chrome | £ Call |
| AE208732R9 | F56V2W | 200°F | 93°C | Poly White | £ Call |
| | | °F | °C | | £ Call |
| | | °F | °C | | £ Call |
| AE288732R9 | F56V3W | 286°F | 141°C | Poly White | £ Call |
| AE361132R9 | F56V6B | 360°F | 182°C | Brass | £ Call |
| AE362132R9 | F56V6C | 360°F | 182°C | Chrome | £ Call |
| AE368732R9 | F56V6W | 360°F | 182°C | White | £ 53.95 |
| MODEL F156 VERTICAL K5.6 (80) BSPT THREADS 1/2" (15MM) RA1385 | | | | | |
| AE131132R2 | F56V0BM | 135°F | 57°C | Brass | £ 43.08 |
| AE132132R2 | F56V0CM | 135°F | 57°C | Chrome | £ 49.35 |
| AE138732R2 | F56V0WM | 135°F | 57°C | White | £ 53.95 |
| AE151132R2 | | 155°F | 68°C | Brass | £ 43.08 |
| AE152132R2 | F56V1CM | 155°F | 68°C | Chrome | £ 49.35 |
| AE158732R2 | F56V1WM | 155°F | 68°C | Poly White | £ 53.95 |
| AE171132R2 | F56V5BM | 175°F | 79°C | Brass | £ 43.08 |
| AE172132R2 | F56V5CM | 175°F | 79°C | Chrome | £ 49.35 |
| AE178732R2 | F56V5WM | 175°F | 79°C | White | £ 53.95 |
| AE201132R2 | F56V2BM | 200°F | 93°C | Brass | £ 43.08 |
| AE202132R2 | F56V2CM | 200°F | 93°C | Chrome | £ 49.35 |
| AE208732R2 | F56V2WM | 200°F | 93°C | Poly White | £ 53.95 |
| AE281132R2 | F56V3BM | 286°F | 141°C | Brass | £ 43.08 |
| AE282132R2 | F56V3CM | 286°F | 141°C | Chrome | £ 49.35 |
| AE288732R2 | F56V3WM | 286°F | 141°C | Poly White | £ 53.95 |
| AE361132R2 | F56V6BM | 360°F | 182°C | Brass | £ 43.08 |
| AE362132R2 | F56V6CM | 360°F | 182°C | Chrome | £ 49.35 |
| AE368732R2 | F56V6WM | 360°F | 182°C | White | £ 53.95 |

6880050100 WW2 Requires Model W2 Sprinkler Wrench £ 114.28



G UPRIGHT

- K5.6 = SIN R1025
- K7.96 = SIN R1026 (17/32"x1/2")
- K8.2 = SIN R1027
- See Bulletin 110

| Part Number | Short Code | Temperature | | Finish | List Price |
|---|------------|-------------|-------|------------|------------|
| MODEL G UPRIGHT K5.6 (80) THREADS 1/2" (15MM) R1025 | | | | | |
| 5113113299 | GU0B | 135°F | 57°C | Brass | £ 40.35 |
| 5113213299 | GU0C | 135°F | 57°C | Chrome | £ 48.00 |
| 5113873299 | GU0W | 135°F | 57°C | White | £ 52.79 |
| 5116113299 | GU1B | 165°F | 74°C | Brass | £ 40.35 |
| 5116213299 | GU1C | 165°F | 74°C | Chrome | £ 48.00 |
| 5116873299 | GU1W | 165°F | 74°C | Poly White | £ 52.79 |
| 5121113299 | GU2B | 212°F | 100°C | Brass | £ 40.35 |
| 5121213299 | GU2C | 212°F | 100°C | Chrome | £ 48.00 |
| 5121873299 | GU2W | 212°F | 100°C | White | £ 52.79 |
| 5128113299 | GU3B | 286°F | 141°C | Brass | £ 40.35 |
| 5128213299 | GU3C | 286°F | 141°C | Chrome | £ 48.00 |
| 5128873299 | GU3W | 286°F | 141°C | White | £ 52.79 |
| MODEL G UPRIGHT K8.2 (115) THREADS 3/4" (20MM) R1027 | | | | | |
| 5113113498 | GU0LB | 135°F | 57°C | Brass | £ 48.41 |
| 5113213498 | GU0LC | 135°F | 57°C | Chrome | £ 58.16 |
| 5116113498 | GU1LB | 165°F | 74°C | Brass | £ 48.41 |
| 5116213498 | GU1LC | 165°F | 74°C | Chrome | £ 58.16 |
| 5121113498 | GU2LB | 212°F | 100°C | Brass | £ 48.41 |
| 5121213498 | GU2LC | 212°F | 100°C | Chrome | £ 58.16 |
| 5128113498 | GU3LB | 286°F | 141°C | Brass | £ 48.41 |
| 5128213498 | GU3LC | 286°F | 141°C | Chrome | £ 58.16 |
| MODEL G UPRIGHT K8.0 (115) THREADS 1/2" (15MM) R1026 | | | | | |
| 5113113499 | GU0LHB | 135°F | 57°C | Brass | £ 62.16 |
| 5113213499 | GU0LHC | 135°F | 57°C | Chrome | £ 71.19 |
| 5116113499 | GU1LHB | 165°F | 74°C | Brass | £ 62.16 |
| 5116213499 | GU1LHC | 165°F | 74°C | Chrome | £ 71.19 |
| 5121113499 | GU2LHB | 212°F | 100°C | Brass | £ 62.16 |
| 5121213499 | GU2LHC | 212°F | 100°C | Chrome | £ 71.19 |
| 5128113499 | GU3LHB | 286°F | 141°C | Brass | £ 62.16 |
| 5128213499 | GU3LHC | 286°F | 141°C | Chrome | £ 71.19 |

6880050100 WW2 Wrench, W2, Pendent, Upright, HSW £ 114.28



G UPRIGHT

- K2.82 = SIN R1021
- K4.24 = SIN R1023
- K4.10 = SIN R1024
- See Bulletin 110

| Part Number | Short Code | Temperature | | Finish | List Price |
|--|------------|-------------|-------|--------|------------|
| MODEL G UPRIGHT K2.8 (40) THREADS 1/2" (15MM) R1021 | | | | | |
| 5113112499 | GU03B | 135°F | 57°C | Brass | £ 55.26 |
| 5113212499 | GU03C | 135°F | 57°C | Chrome | £ 64.14 |
| 5116112499 | GU13B | 165°F | 74°C | Brass | £ 55.26 |
| 5116212499 | GU13C | 165°F | 74°C | Chrome | £ 64.14 |
| 5121112499 | GU23B | 212°F | 100°C | Brass | £ 55.26 |
| 5121212499 | GU23C | 212°F | 100°C | Chrome | £ 64.14 |
| 5128112499 | GU33B | 286°F | 141°C | Brass | £ 55.26 |
| 5128212499 | GU33C | 286°F | 141°C | Chrome | £ 64.14 |
| MODEL G UPRIGHT K4.2 (60) THREADS 1/2" (15MM) R1023 | | | | | |
| 5113112899 | GU07B | 135°F | 57°C | Brass | £ 55.26 |
| 5113212899 | GU07C | 135°F | 57°C | Chrome | £ 64.14 |
| 5116112899 | GU17B | 165°F | 74°C | Brass | £ 55.26 |
| 5116212899 | GU17C | 165°F | 74°C | Chrome | £ 64.14 |
| 5121112899 | GU27B | 212°F | 100°C | Brass | £ 55.26 |
| 5128112899 | GU37B | 286°F | 141°C | Brass | £ 55.26 |
| 5128212899 | GU37C | 286°F | 141°C | Chrome | £ 64.14 |

| | | | |
|------------|-----|--------------------------------|----------|
| 6880050100 | WW2 | WRENCH,W2(PENDENT,UPRIGHT,HSW) | £ 114.28 |
|------------|-----|--------------------------------|----------|



G PENDENT

- K5.6 = SIN R1015
- K8.2 = SIN R1017
- See Bulletin 110

| Part Number | Short Code | Temperature | | Finish | List Price |
|---|------------|-------------|-------|------------|------------|
| MODEL G PENDENT K5.6 (80) THREADS 1/2" (15MM) R1015 | | | | | |
| 5213113299 | GP0B | 135°F | 57°C | Brass | £ 40.35 |
| 5213213299 | GP0C | 135°F | 57°C | Chrome | £ 46.75 |
| 5213873299 | GP0W | 135°F | 57°C | White | £ 52.79 |
| 5216113299 | GP1B | 165°F | 74°C | Brass | £ 40.35 |
| 5216213299 | GP1C | 165°F | 74°C | Chrome | £ 46.75 |
| 5216873299 | GP1W | 165°F | 74°C | Poly White | £ 52.79 |
| 5221113299 | GP2B | 212°F | 100°C | Brass | £ 40.35 |
| 5221213299 | GP2C | 212°F | 100°C | Chrome | £ 46.75 |
| 5221873299 | GP2W | 212°F | 100°C | White | £ 52.79 |
| 5228113299 | GP3B | 286°F | 141°C | Brass | £ 40.35 |
| 5228213299 | GP3C | 286°F | 141°C | Chrome | £ 46.75 |
| 5228873299 | GP3W | 286°F | 141°C | White | £ 52.79 |
| MODEL G PENDENT K8.0 (115) THREADS 3/4" (20MM) R1017 | | | | | |
| 5213113498 | GP0LB | 135°F | 57°C | Brass | £ 49.72 |
| 5213213498 | GP0LC | 135°F | 57°C | Chrome | £ 58.16 |
| 5216113498 | GP1LB | 165°F | 74°C | Brass | £ 49.72 |
| 5216213498 | GP1LC | 165°F | 74°C | Chrome | £ 58.16 |
| 5221113498 | GP2LB | 212°F | 100°C | Brass | £ 49.72 |
| 5221213498 | GP2LC | 212°F | 100°C | Chrome | £ 58.16 |
| 5228113498 | GP3LB | 286°F | 141°C | Brass | £ 49.72 |
| 5228213498 | GP3LC | 286°F | 141°C | Chrome | £ 58.16 |
| MODEL F1 RECESSED ESCUTCHEONS & COLLAR ASSEMBLY | | | | | |
| 6800630001 | GF1B | 1/2" (15mm) | | Brass | £ 20.97 |
| 6800600001 | GF1C | 1/2" (15mm) | | Chrome | £ 11.30 |
| 6800640001 | GF1W | 1/2" (15mm) | | White | £ 11.30 |
| 6801030000 | GF1LB | 3/4" (20mm) | | Brass | £ 20.97 |
| 6801000000 | GF1LC | 3/4" (20mm) | | Chrome | £ 11.30 |
| 6801040000 | GF1LW | 3/4" (20mm) | | White | £ 11.30 |
| 6800930000 | GF1MB | 10mm | | Brass | £ 20.96 |
| 6800900000 | GF1MC | 10mm | | Chrome | £ 11.16 |
| 6800940003 | GF1MW | 10mm | | Poly White | £ 11.16 |

| | | | |
|------------|-----|-----------------------------------|----------|
| 6880050100 | WW2 | Wrench, W2, Pendent, Upright, HSW | £ 114.28 |
| 6880100000 | WRC | For Recessed Use RC1 Wrench | £ 339.15 |



G PENDENT

- K7.96 = SIN R1016
- K2.82 = SIN R1011
- K4.24 = SIN R1013
- K4.10 = SIN R1014
- See Bulletin 110

| Part Number | Short Code | Temperature | | Finish | List Price |
|--|------------|-------------|-------|--------|------------|
| MODEL G PENDENT K2.8 (40) THREADS 1/2" (15MM) R1011 | | | | | |
| 5213112499 | GP03B | 135°F | 57°C | Brass | £ 55.26 |
| 5213212499 | GP03C | 135°F | 57°C | Chrome | £ 64.14 |
| 5216112499 | GP13B | 165°F | 74°C | Brass | £ 55.26 |
| 5216212499 | GP13C | 165°F | 74°C | Chrome | £ 64.14 |
| 5221112499 | GP23B | 212°F | 100°C | Brass | £ 55.26 |
| 5221212499 | GP23C | 212°F | 100°C | Chrome | £ 64.14 |
| 5228112499 | GP33B | 286°F | 141°C | Brass | £ 55.26 |
| 5228212499 | GP33C | 286°F | 141°C | Chrome | £ 64.14 |
| MODEL G PENDENT K4.2 (60) THREADS 1/2" (15MM) R1013 | | | | | |
| 5213112899 | GP07B | 135°F | 57°C | Brass | £ 55.26 |
| 5213212899 | GP07C | 135°F | 57°C | Chrome | £ 64.14 |
| 5216112899 | GP17B | 165°F | 74°C | Brass | £ 55.26 |
| 5216212899 | GP17C | 165°F | 74°C | Chrome | £ 64.14 |
| 5221112899 | GP27B | 212°F | 100°C | Brass | £ 55.26 |
| 5221212899 | GP27C | 212°F | 100°C | Chrome | £ 64.14 |
| 5228112899 | GP37B | 286°F | 141°C | Brass | £ 55.26 |
| 5228212899 | GP37C | 286°F | 141°C | Chrome | £ 64.14 |

| | | | | |
|------------|-----|------------------------------------|--|----------|
| 6880050100 | WW2 | Wrench, W2, Pendent, Upright, HSW | | £ 114.28 |
| 6880100000 | WRC | For Recessed, Use Model RC1 Wrench | | £ 339.15 |



G VSW

- K-Factor = 5.6 (80)
- **SIN R1285**
- See Bulletin 112

| Part Number | Short Code | Temperature | | Finish | List Price |
|---|------------|-------------|-------|--------|------------|
| MODEL G VERTICAL K5.6 (80) THREADS 1/2" (15MM) R1285 | | | | | |
| 5413113292 | GV0B | 135°F | 57°C | Brass | £ 58.49 |
| 5413213292 | GV0C | 135°F | 57°C | Chrome | £ 66.16 |
| 5416113292 | GV1B | 165°F | 74°C | Brass | £ 58.49 |
| 5416213292 | GV1C | 165°F | 74°C | Chrome | £ 66.16 |
| 5421113292 | GV2B | 212°F | 100°C | Brass | £ 58.49 |
| 5421213292 | GV2C | 212°F | 100°C | Chrome | £ 66.16 |
| 5428113292 | GV3B | 286°F | 141°C | Brass | £ 58.49 |
| 5428213292 | GV3C | 286°F | 141°C | Chrome | £ 66.16 |

| | | | |
|------------|-----|-----------------------------------|----------|
| 6880050100 | WW2 | Wrench, W2, Pendent, Upright, HSW | £ 114.28 |
|------------|-----|-----------------------------------|----------|




G HSW

- K5.6 = SIN R1235
- K8.0 w 3/4"NPT = SIN R1237
- K8.0 w 1/2"NPT = SIN R1236
- See Bulletin 112

| Part Number | Short Code | Temperature | | Finish | List Price |
|--|------------|-------------|-------|------------|------------|
| MODEL G HORIZONTAL K5.6 (80) THREADS 1/2" (15MM) R1235 | | | | | |
| 5413113299 | GH0B | 135°F | 57°C | Brass | £ 57.11 |
| 5413213299 | GH0C | 135°F | 57°C | Chrome | £ 64.59 |
| 5416113299 | GH1B | 165°F | 74°C | Brass | £ 57.11 |
| 5416213299 | GH1C | 165°F | 74°C | Chrome | £ 64.59 |
| 5421113299 | GH2B | 212°F | 100°C | Brass | £ 57.11 |
| 5421213299 | GH2C | 212°F | 100°C | Chrome | £ 64.59 |
| 5428113299 | GH3B | 286°F | 141°C | Brass | £ 57.11 |
| 5428213299 | GH3C | 286°F | 141°C | Chrome | £ 64.59 |
| MODEL G HORIZONTAL K8.0 (115) THREADS 3/4" (20MM) R1237 | | | | | |
| 5413113498 | GH0LB | 135°F | 57°C | Brass | £ 64.51 |
| 5413213498 | GH0LC | 135°F | 57°C | Chrome | £ 71.38 |
| 5416113498 | GH1LB | 165°F | 74°C | Brass | £ 64.51 |
| 5416213498 | GH1LC | 165°F | 74°C | Chrome | £ 71.38 |
| 5421113498 | GH2LB | 212°F | 100°C | Brass | £ 64.51 |
| 5421213498 | GH2LC | 212°F | 100°C | Chrome | £ 71.38 |
| 5428113498 | GH3LB | 286°F | 141°C | Brass | £ 64.51 |
| 5428213498 | GH3LC | 286°F | 141°C | Chrome | £ 71.38 |
| MODEL G HORIZONTAL K8.0 (115) THREADS 1/2" (15MM) 1236 | | | | | |
| 5413113499 | GH0LHB | 135°F | 57°C | Brass | £ 77.07 |
| 5413213499 | GH0LHC | 135°F | 57°C | Chrome | £ 83.87 |
| 5416113499 | GH1LHB | 165°F | 74°C | Brass | £ 77.07 |
| 5416213499 | GH1LHC | 165°F | 74°C | Chrome | £ 83.87 |
| 5421113499 | GH2LHB | 212°F | 100°C | Brass | £ 77.07 |
| 5421213499 | GH2LHC | 212°F | 100°C | Chrome | £ 83.87 |
| 5428113499 | GH3LHB | 286°F | 141°C | Brass | £ 77.07 |
| 5428213499 | GH3LHC | 286°F | 141°C | Chrome | £ 83.87 |
| MODEL F1 RECESSED ESCUTCHEONS & COLLAR ASSEMBLY | | | | | |
| 6800630001 | GF1B | 1/2" (15mm) | | Brass | £ 20.97 |
| 6800600001 | GF1C | 1/2" (15mm) | | Chrome | £ 11.30 |
| 6800640001 | GF1W | 1/2" (15mm) | | White | £ 11.30 |
| 6801030000 | GF1LB | 3/4" (20mm) | | Brass | £ 20.97 |
| 6801000000 | GF1LC | 3/4" (20mm) | | Chrome | £ 11.30 |
| 6801040000 | GF1LW | 3/4" (20mm) | | White | £ 11.30 |
| 6800930000 | GF1MB | 10mm | | Brass | £ 20.96 |
| 6800900000 | GF1MC | 10mm | | Chrome | £ 11.16 |
| 6800940003 | GF1MW | 10mm | | Poly White | £ 11.16 |


| | | | |
|------------|-----|-----------------------------------|----------|
| 6880050100 | WW2 | Wrench, W2, Pendent, Upright, HSW | £ 114.28 |
| 6880100120 | WW4 | Wrench, W4, Recessed, Concealed | £ 339.15 |



G HSW

- K2.8 = SIN R1231
- K4.2 = SIN R1233
- See Bulletin 112

| Part Number | Short Code | Temperature | | Finish | List Price |
|---|------------|-----------------------------------|-------|------------|------------|
| MODEL G HORIZONTAL K2.8 (40) THREADS 1/2" (15MM) R1231 | | | | | |
| 5413112499 | GH03B | 135°F | 57°C | Brass | £ 71.38 |
| 5413212499 | GH03C | 135°F | 57°C | Chrome | £ 77.89 |
| 5416112499 | GH13B | 165°F | 74°C | Brass | £ 71.38 |
| 5416212499 | GH13C | 165°F | 74°C | Chrome | £ 77.89 |
| 5421112499 | GH23B | 212°F | 100°C | Brass | £ 71.38 |
| 5421212499 | GH23C | 212°F | 100°C | Chrome | £ 77.89 |
| 5428112499 | GH33B | 286°F | 141°C | Brass | £ 71.38 |
| 5428212499 | GH33C | 286°F | 141°C | Chrome | £ 77.89 |
| MODEL G HORIZONTAL K4.2 (60) THREADS 1/2" (15MM) R1233 | | | | | |
| 5413112899 | GH07B | 135°F | 57°C | Brass | £ 71.38 |
| 5413212899 | GH07C | 135°F | 57°C | Chrome | £ 77.89 |
| 5416112899 | GH17B | 165°F | 74°C | Brass | £ 71.38 |
| 5416212899 | GH17C | 165°F | 74°C | Chrome | £ 77.89 |
| 5421112899 | GH27B | 212°F | 100°C | Brass | £ 71.38 |
| 5421212899 | GH27C | 212°F | 100°C | Chrome | £ 77.89 |
| 5428112899 | GH37B | 286°F | 141°C | Brass | £ 71.38 |
| 5428212899 | GH37C | 286°F | 141°C | Chrome | £ 77.89 |
| MODEL F1 RECESSED ESCUTCHEONS & COLLAR ASSEMBLY | | | | | |
| 6800630001 | GF1B | 1/2" (15mm) | | Brass | £ 20.97 |
| 6800600001 | GF1C | 1/2" (15mm) | | Chrome | £ 11.30 |
| 6800640001 | GF1W | 1/2" (15mm) | | White | £ 11.30 |
| 6801030000 | GF1LB | 3/4" (20mm) | | Brass | £ 20.97 |
| 6801000000 | GF1LC | 3/4" (20mm) | | Chrome | £ 11.30 |
| 6801040000 | GF1LW | 3/4" (20mm) | | White | £ 11.30 |
| 6800930000 | GF1MB | 10mm | | Brass | £ 20.96 |
| 6800900000 | GF1MC | 10mm | | Chrome | £ 11.16 |
| 6800940003 | GF1MW | 10mm | | Poly White | £ 11.16 |
| 6880050100 | WW2 | Wrench, W2, Pendent, Upright, HSW | | | £ 114.28 |
| 6880100120 | WW4 | Wrench, W4, Recessed, Concealed | | | £ 339.15 |



G RECESSED

Non-Adjustable -


- K2.8 = SIN R1011
- K4.2 = SIN R1013
- K5.6 = SIN R1015
- K8.0 = SIN R1016
- See Bulletin 111

| Part Number | Short Code | Temperature | | Finish | List Price |
|--|------------|-------------|-------|------------|------------|
| MODEL G RECESSED K5.6 (80) THREADS 1/2" (15MM) R1015 | | | | | |
| 5513343270 | GR0B | 135°F | 57°C | W/O | £ 59.38 |
| 5513323270 | GR0C | 135°F | 57°C | W/O | £ 54.84 |
| 5513463270 | GR0W | 135°F | 57°C | Poly White | £ 59.38 |
| 5516343270 | GR1B | 165°F | 74°C | Brass | £ 59.38 |
| 5516323270 | GR1C | 165°F | 74°C | Chrome | £ 54.84 |
| 5516463270 | GR1W | 165°F | 74°C | Poly White | £ 59.38 |
| 5521343270 | GR2B | 212°F | 100°C | W/O | £ 59.38 |
| 5521323270 | GR2C | 212°F | 100°C | Chrome | £ 54.84 |
| 5521463270 | GR2W | 212°F | 100°C | W/O | £ 59.38 |
| MODEL G RECESSED K8.0 (115) THREADS 1/2" (15MM) R1016 | | | | | |
| 5513343470 | GR0LHB | 135°F | 57°C | W/O | £ 72.14 |
| 5513323470 | GR0LHC | 135°F | 57°C | W/O | £ 70.12 |
| 5516343470 | GR1LHB | 165°F | 74°C | Brass | £ 72.14 |
| 5516323470 | GR1LHC | 165°F | 74°C | Chrome | £ 70.12 |
| 5521343470 | GR2LHB | 212°F | 100°C | W/O | £ 72.14 |
| 5521323470 | GR2LHC | 212°F | 100°C | Chrome | £ 70.12 |
| MODEL G RECESSED K2.8 (40) THREADS 1/2" (15MM) R1011 | | | | | |
| 5513342470 | GR03B | 135°F | 57°C | W/O | £ 80.84 |
| 5513322470 | GR03C | 135°F | 57°C | W/O | £ 76.71 |
| 5516342470 | GR13B | 165°F | 74°C | Brass | £ 80.84 |
| | | °F | °C | | £ Call |
| 5521342470 | GR23B | 212°F | 100°C | W/O | £ 80.84 |
| 5521322470 | GR23C | 212°F | 100°C | Chrome | £ 76.71 |
| MODEL G RECESSED ESCUTCHEONS | | | | | |
| 6801361101 | GRB | Threaded | | Brass | £ 33.50 |
| 6801362101 | GRC | Threaded | | Chrome | £ 17.52 |
| 6801367201 | GRW | Threaded | | White | £ 17.52 |
| 6801369001 | GRSP | Threaded | | Specialty | £ 43.09 |

6880100000 WRC Requires Model RC1 Sprinkler Wrench £ 339.15

Notes:

Sprinklers and Escutcheons sold and packaged separately



G (CONT.)

- K4.2 = SIN R1013
- K5.6 1" M AND 1" F SIN R1118
- See Bulletin 111

| Part Number | Short Code | Temperature | | Finish | List Price |
|---|------------|-------------|-------|-----------|------------|
| MODEL G RECESSED K4.2 (40) THREADS 1/2" (15MM) R1013 | | | | | |
| 5513342870 | GR07B | 135°F | 57°C | W/O | £ 80.84 |
| 5513322870 | GR07C | 135°F | 57°C | W/O | £ 76.71 |
| 5516342870 | GR17B | 165°F | 74°C | Brass | £ 80.84 |
| | | °F | °C | | £ Call |
| 5521342870 | GR27B | 212°F | 100°C | W/O | £ 80.84 |
| 5521322870 | GR27C | 212°F | 100°C | Chrome | £ 76.71 |
| MODEL G RECESSED ESCUTCHEONS | | | | | |
| 6801361101 | GRB | Threaded | | Brass | £ 33.50 |
| 6801362101 | GRC | Threaded | | Chrome | £ 17.52 |
| 6801367201 | GRW | Threaded | | White | £ 17.52 |
| 6801369001 | GRSP | Threaded | | Specialty | £ 43.09 |

6880100000 WRC For Recessed Use Model RC1 Wrench £ 339.15

Notes:

Sprinklers and Escutcheons sold and packaged separately



G4 CONCEALED

- K2.8 = SIN R2111
- K4.2 = SIN R2113
- K5.6 = SIN R2115
- See Bulletin 121

| Sprinkler | Coverplate |
|-------------|------------|
| 135°F/57°C | 135°F/57°C |
| 165°F/74°C | 165°F/74°C |
| 212°F/100°C | 165°F/74°C |

| Part Number | Short Code | Temperature | Finish | List Price |
|---|------------|-------------|-----------------|------------|
| MODEL G4 CONCEALED K5.6 (80) THREADS 1/2" (15MM) R2115 | | | | |
| 5713173299 | G40 | 135°F 57°C | W/O | £ 58.10 |
| 5716173299 | G41 | 165°F 74°C | W/O | £ 56.38 |
| 5721173299 | G42 | 212°F 100°C | W/O | £ 58.10 |
| MODEL G4 CONCEALED K2.8 (40) THREADS 1/2" (15MM) R2111 | | | | |
| 5713172499 | G403 | 135°F 57°C | W/O | £ 62.00 |
| 5716172499 | G413 | 165°F 74°C | W/O | £ 62.00 |
| 5721172499 | G423 | 212°F 100°C | W/O | £ 62.00 |
| MODEL G4 CONCEALED K4.2 (60) THREADS 1/2" (15MM) R2113 | | | | |
| 5713172899 | G407 | 135°F 57°C | W/O | £ 62.00 |
| 5716172899 | G417 | 165°F 74°C | W/O | £ 62.00 |
| 5721172899 | G427 | 212°F 100°C | W/O | £ 62.00 |
| MODEL G5 COVER PLATES | | | | |
| 6887271321 | CG50C | 135°F 57°C | Chrome | £ 41.97 |
| 6887271372 | CG50W | 135°F 57°C | White | £ 38.26 |
| 6887271390 | CG50SP | 135°F 57°C | Specialty | £ 54.12 |
| 6887271374 | CG50OW | 135°F 57°C | Off-White | £ 52.03 |
| 6887271316 | CG50FB | 135°F 57°C | Black Painted | £ 52.10 |
| 6887271305 | CG50BB | 135°F 57°C | Bright Brass | £ 66.05 |
| 6887271323 | CG50CD | 135°F 57°C | Satin Chrome | £ 66.05 |
| 6887271310 | CG50SS | 135°F 57°C | Stainless Steel | £ 66.05 |
| 6887271311 | CG50B | 135°F 57°C | Finished Bronze | £ 54.56 |
| 6887271319 | CG50EW | 135°F 57°C | Euro White | £ 38.26 |
| 6887271621 | CG51C | 165°F 74°C | Chrome | £ 41.97 |
| 6887271672 | CG51W | 165°F 74°C | White | £ 38.26 |
| 6887271690 | CG51SP | 165°F 74°C | Specialty | £ 54.12 |
| 6887271674 | CG51OW | 165°F 74°C | Off-White | £ 52.03 |
| 6887271690 | CG51SP | 165°F 74°C | Specialty | £ 54.12 |
| 6887271616 | CG51FB | 165°F 74°C | Black Painted | £ 52.10 |
| 6887271605 | CG51BB | 165°F 74°C | Bright Brass | £ 66.05 |
| 6887271623 | CG51CD | 165°F 74°C | Satin Chrome | £ 66.05 |
| 6887271610 | CG51SS | 165°F 74°C | Stainless Steel | £ 66.05 |
| 6887271619 | CG51EW | 165°F 74°C | Euro White | £ 38.26 |

6880170000 WG4 Requires Model G4 Sprinkler Wrench £ 337.83

Notes:

Sprinklers and coverplates sold and packaged separately



G4 -11CONCEALED

- K11.2 = SIN R101
- See Bulletin 086

| Part Number | Short Code | Temperature | | Finish | List Price |
|---|------------|------------------------------------|-------|-----------------|------------|
| MODEL G4 -11 CONCEALED K11.2 (160) THREADS 3/4" R101 | | | | | |
| 1716173698 | G4111 | 165°F | 74°C | W/O | £ 124.63 |
| 1721173698 | G4112 | 212°F | 100°C | W/O | £ 124.63 |
| MODEL G5 SR GASKET COVER PLATES | | | | | |
| 6887031372 | CG4S0W | 135°F | 57°C | White | £ 97.85 |
| 6887031672 | CG4S1W | 165°F | 74°C | White | £ 97.85 |
| MODEL G5 QR GASKET COVER PLATES | | | | | |
| 6887201372 | CG5S0W | 135°F | 57°C | White | £ 97.85 |
| 6887201672 | CG5S1W | 165°F | 74°C | White | £ 97.85 |
| MODEL G5 COVER PLATES | | | | | |
| 6887271321 | CG50C | 135°F | 57°C | Chrome | £ 41.97 |
| 6887271372 | CG50W | 135°F | 57°C | White | £ 38.26 |
| 6887271390 | CG50SP | 135°F | 57°C | Specialty | £ 54.12 |
| 6887271374 | CG50OW | 135°F | 57°C | Off-White | £ 52.03 |
| 6887271316 | CG50FB | 135°F | 57°C | Black Painted | £ 52.10 |
| 6887271305 | CG50BB | 135°F | 57°C | Bright Brass | £ 66.05 |
| 6887271323 | CG50CD | 135°F | 57°C | Satin Chrome | £ 66.05 |
| 6887271310 | CG50SS | 135°F | 57°C | Stainless Steel | £ 66.05 |
| 6887271311 | CG50B | 135°F | 57°C | Finished Bronze | £ 54.56 |
| 6887271319 | CG50EW | 135°F | 57°C | Euro White | £ 38.26 |
| 6887271621 | CG51C | 165°F | 74°C | Chrome | £ 41.97 |
| 6887271672 | CG51W | 165°F | 74°C | White | £ 38.26 |
| 6887271690 | CG51SP | 165°F | 74°C | Specialty | £ 54.12 |
| 6887271674 | CG51OW | 165°F | 74°C | Off-White | £ 52.03 |
| 6887271690 | CG51SP | 165°F | 74°C | Specialty | £ 54.12 |
| 6887271616 | CG51FB | 165°F | 74°C | Black Painted | £ 52.10 |
| 6887271605 | CG51BB | 165°F | 74°C | Bright Brass | £ 66.05 |
| 6887271623 | CG51CD | 165°F | 74°C | Satin Chrome | £ 66.05 |
| 6887271610 | CG51SS | 165°F | 74°C | Stainless Steel | £ 66.05 |
| 6887271619 | CG51EW | 165°F | 74°C | Euro White | £ 38.26 |
| 6880170000 | WG4 | Requires Model G4 Sprinkler Wrench | | | £ 337.83 |

Notes:

Sprinklers and coverplates sold and packaged separately



**G4-300
 CONCEALED**

- K-Factor = 5.6 (80)
- **SIN R6115**
- See Bulletin 161

| Sprinkler | Coverplate |
|-------------|------------|
| 135°F/57°C | 135°F/57°C |
| 165°F/74°C | 165°F/74°C |
| 212°F/100°C | 165°F/74°C |

| Part Number | Short Code | Temperature | | Finish | List Price |
|---|------------|-------------|-------|-----------------|------------|
| MODEL G4 - 300 CONCEALED K5.6 (80) THREADS 1/2" (15MM) R6115 | | | | | |
| 57A1173299 | G40300 | 135°F | 57°C | W/O | £ 60.20 |
| 57A2173299 | G41300 | 165°F | 74°C | W/O | £ 60.20 |
| 57A6173299 | G42300 | 212°F | 100°C | W/O | £ 60.20 |
| MODEL G5 COVER PLATES | | | | | |
| 6887271321 | CG50C | 135°F | 57°C | Chrome | £ 41.97 |
| 6887271372 | CG50W | 135°F | 57°C | White | £ 38.26 |
| 6887271311 | CG50B | 135°F | 57°C | Finished Bronze | £ 54.56 |
| 6887271374 | CG50OW | 135°F | 57°C | Off-White | £ 52.03 |
| 6887271390 | CG50SP | 135°F | 57°C | Specialty | £ 54.12 |
| 6887271316 | CG50FB | 135°F | 57°C | Black Painted | £ 52.10 |
| 6887271305 | CG50BB | 135°F | 57°C | Bright Brass | £ 66.05 |
| 6887271323 | CG50CD | 135°F | 57°C | Satin Chrome | £ 66.05 |
| 6887271310 | CG50SS | 135°F | 57°C | Stainless Steel | £ 66.05 |
| 6887271319 | CG50EW | 135°F | 57°C | Euro White | £ 38.26 |
| 6887271621 | CG51C | 165°F | 74°C | Chrome | £ 41.97 |
| 6887271672 | CG51W | 165°F | 74°C | White | £ 38.26 |
| 6887271611 | CG51B | 165°F | 74°C | Finished Bronze | £ 54.56 |
| 6887271674 | CG51OW | 165°F | 74°C | Off-White | £ 52.03 |
| 6887271690 | CG51SP | 165°F | 74°C | Specialty | £ 54.12 |
| 6887271616 | CG51FB | 165°F | 74°C | Black Painted | £ 52.10 |
| 6887271605 | CG51BB | 165°F | 74°C | Bright Brass | £ 66.05 |
| 6887271623 | CG51CD | 165°F | 74°C | Satin Chrome | £ 66.05 |
| 6887271610 | CG51SS | 165°F | 74°C | Stainless Steel | £ 66.05 |
| 6887271619 | CG51EW | 165°F | 74°C | Euro White | £ 38.26 |

6880170000 WG4 Requires Model G4 Sprinkler Wrench £ 337.83

Notes:

Sprinklers and coverplates sold and packaged separately



G5-80F

- K-Factor = 8.0(115)
- **SIN RA3417**
- See Bulletin 034

| Part Number | Short Code | Temperature | | Finish | List Price |
|--|------------|-------------|-------|-----------------|------------|
| MODEL G5-80F CONCEALED K8.0 (115) THREADS 3/4" (20MM) RA3417 | | | | | |
| 1916173497 | G5801BFM | 165°F | 74°C | W/O | £ 77.73 |
| 1921173497 | G5802BFM | 212°F | 100°C | W/O | £ 77.73 |
| MODEL G5-80F CONCEALED K8.0 (115) THREADS BSPT 3/4" (20MM) RA3417 | | | | | |
| 1916173494 | G5801MFM | 165°F | 74°C | W/O | £ 77.73 |
| 1921173494 | G5802MFM | 212°F | 100°C | W/O | £ 77.73 |
| MODEL G5 COVERPLATES | | | | | |
| 6887271321 | CG50C | 135°F | 57°C | Chrome | £ 41.97 |
| 6887271372 | CG50W | 135°F | 57°C | White | £ 38.26 |
| 6887271311 | CG50B | 135°F | 57°C | Finished Bronze | £ 54.56 |
| 6887271374 | CG50OW | 135°F | 57°C | Off-White | £ 52.03 |
| 6887271390 | CG50SP | 135°F | 57°C | Specialty | £ 54.12 |
| 6887271316 | CG50FB | 135°F | 57°C | Black Painted | £ 52.10 |
| 6887271305 | CG50BB | 135°F | 57°C | Bright Brass | £ 66.05 |
| 6887271323 | CG50CD | 135°F | 57°C | Satin Chrome | £ 66.05 |
| 6887271310 | CG50SS | 135°F | 57°C | Stainless Steel | £ 66.05 |
| 6887271319 | CG50EW | 135°F | 57°C | Euro White | £ 38.26 |
| 6887271621 | CG51C | 165°F | 74°C | Chrome | £ 41.97 |
| 6887271672 | CG51W | 165°F | 74°C | White | £ 38.26 |
| 6887271611 | CG51B | 165°F | 74°C | Finished Bronze | £ 54.56 |
| 6887271674 | CG51OW | 165°F | 74°C | Off-White | £ 52.03 |
| 6887271690 | CG51SP | 165°F | 74°C | Specialty | £ 54.12 |
| 6887271616 | CG51FB | 165°F | 74°C | Black Painted | £ 52.10 |
| 6887271605 | CG51BB | 165°F | 74°C | Bright Brass | £ 66.05 |
| 6887271610 | CG51SS | 165°F | 74°C | Stainless Steel | £ 66.05 |
| 6887271623 | CG51CD | 165°F | 74°C | Satin Chrome | £ 66.05 |
| 6887271619 | CG51EW | 165°F | 74°C | Euro White | £ 38.26 |

| | | | |
|------------|-----|--|----------|
| 6880170020 | WFC | WRENCH,FC,CONCEALED | £ 340.96 |
| 6880100110 | W3 | WRENCH W3 FOR WRENCH-ABLE PROTECTIVE CAP | £ 340.96 |

Notes:

Factory Mutual does not recognize or approve fully concealed as Quick Response. sprinklers



G5-80 SR "Sealing" Concealed

- K-Factor = 8.0 (115)
- **SIN RA3412**
- See Bulletin 034

G5-80F "Sealing" Concealed

- K-Factor = 8.0 (115)
- **SIN RA3417**
- See Bulletin 034

G5-56 SR "Sealing" Concealed

- K-Factor = 5.6 (80)
- **SIN RA3415**
- See Bulletin 034

G5-42 SR "Sealing" Concealed

- K-Factor = 4.2 (60)
- **SIN RA3413**
- See Bulletin 034

G5-28 SR "Sealing" Concealed

- K-Factor = 2.8 (40)
- **SIN RA3411**
- See Bulletin 034

| Part Number | Short Code | Temperature | Finish | List Price |
|---|------------|-------------|-----------------|------------|
| MODEL G5-80 SR SEALING CONCEALED K8.0 (115) THREADS 3/4" (20MM) RA3412 | | | | |
| 1916173498 | G5801B | 165°F 74°C | W/O | £ 73.69 |
| 1921173498 | G5802B | 212°F 100°C | W/O | £ 73.69 |
| MODEL G5-80F SEALING CONCEALED K8.0 (115) 3/4" (20MM) RA3417 | | | | |
| 1916173497 | G5801BFM | 165°F 74°C | W/O | £ 77.73 |
| 1921173497 | G5802BFM | 212°F 100°C | W/O | £ 77.73 |
| MODEL G5-80F SEALING CONCEALED K8.0 (115) BSPT 3/4" (20MM) RA3417 | | | | |
| 1916173494 | G5801MFM | 165°F 74°C | W/O | £ 77.73 |
| 1921173494 | G5802MFM | 212°F 100°C | W/O | £ 77.73 |
| MODEL G5-56 SR SEALING CONCEALED K5.6 (80) THREADS 1/2"(15MM) RA3415 | | | | |
| 1916173299 | G51B | 165°F 74°C | W/O | £ 59.42 |
| 1921173299 | G52B | 212°F 100°C | W/O | £ 59.42 |
| MODEL G5-42 SR SEALING CONCEALED K4.2 (60) THREADS 1/2" RA3413 | | | | |
| 1916172899 | G5421B | 165°F 74°C | W/O | £ 73.69 |
| 1921172899 | G5422B | 212°F 100°C | W/O | £ 73.69 |
| MODEL G5-28 SR SEALING CONCEALED K2.8 (40) THREADS 1/2" (15MM) RA3411 | | | | |
| 1916172499 | G5281B | 165°F 74°C | W/O | £ 73.69 |
| 1921172499 | G5282B | 212°F 100°C | W/O | £ 73.69 |
| MODEL G5 SEALING CONCEALED COVER PLATES | | | | |
| 6887031372 | CG4S0W | 135°F 57°C | White | £ 97.85 |
| 6887031672 | CG4S1W | 165°F 74°C | White | £ 97.85 |
| 6887031310 | CG4S0SS | 135°F 57°C | Stainless Steel | £ 105.68 |
| 6887031610 | CG4S1SS | 165°F 74°C | Stainless Steel | £ 105.68 |

| | | | |
|------------|-----|--------------------------|----------|
| 6880170020 | WFC | Requires Model FC Wrench | £ 340.96 |
|------------|-----|--------------------------|----------|

Notes:

Sprinklers and coverplates sold and packaged separately



**G5-56 300 SR
 "Sealing"
 Concealed**

- K-Factor = 5.6 (80)
- **SIN RA4014**
- See Bulletin 034

| Part Number | Short Code | Temperature | | Finish | List Price |
|--|------------|--------------------------|------|-----------------|------------|
| MODEL G5-56 300 SR SEALING CONCEALED K5.6 (80) THREADS 1/2" (15MM) RA4014 | | | | | |
| 2016173299 | G51B3 | 165°F | 74°C | W/O | £ 62.80 |
| MODEL G5 SEALING CONCEALED COVER PLATE | | | | | |
| 6887031372 | CG4S0W | 135°F | 57°C | White | £ 97.85 |
| 6887031672 | CG4S1W | 165°F | 74°C | White | £ 97.85 |
| 6887031310 | CG4S0SS | 135°F | 57°C | Stainless Steel | £ 105.68 |
| 6887031610 | CG4S1SS | 165°F | 74°C | Stainless Steel | £ 105.68 |
| 6880170020 | WFC | Requires Model FC Wrench | | | £ 340.96 |

Notes:
 Sprinklers and coverplates sold and packaged separately